


•INSOLATED TERMINALS




Features

- Isolation obeys the color coded
- Other types on request

Section (mm ²)	Color	Hole	Dimensions (mm)				Reference
			A	L1	L2	L3	
0,5-1,0	Red	M	6,4	17,7	13,2	9,7	IR 1,5-3,2
		M3,5	6,4	17,7	13,2	9,7	IR 1,5-3,7
		M4	6,6	18,5	14,0	9,7	IR 1,5-4
		M5	8,0	20,3	15,8	9,7	IR 1,5-5
		M6	9,8	22,5	18,8	9,7	IR 1,5-6
		M8	13,6	26,3	21,8	9,7	IR 1,5-8
		M10	13,6	26,3	21,8	9,7	IR 1,5-10
1,0-2,5	Blue	M	6,4	18,0	13,5	10,0	IR 2,5-3,2
		M3,5	6,4	18,0	13,5	10,0	IR 2,5-3,7
		M4	6,6	18,5	14,0	10,0	IR 2,5-4
		M5	8,5	21,0	16,5	10,0	IR 2,5-5
		M6	11,0	26,0	21,5	10,0	IR 2,5-6
		M8	12,0	26,5	22,0	10,0	IR 2,5-8
		M10	17,0	31,5	27,0	10,0	IR 2,5-10
4,-6,0	Yellow	M12	17,0	31,5	27,0	10,0	IR 2,5-12
		M3,5	7,8	24,3	17,8	2,5	IR 6-3,7
		M4	7,8	26,0	18,0	13,0	IR 6-4
		M5	10,0	28,0	20,0	13,0	IR 6-5
		M6	11,0	29,5	21,5	13,5	IR 6-6
		M8	14,0	34,0	26,0	13,5	IR 6-8
		M10	15,0	34,5	26,5	13,5	IR 6-10
		M12	17,0	40,0	32,0	13,5	IR 6-12

•INSOLATED FERRULES



Features

- Posted on CU electrolytic 99.9%
- Insulation prolipopileno
- Availability of uninsulated

Section (mm ²)	Packaging units	Reference
0,50	500	E02
0,75	500	E05
1,00	500	E09
1,50	500	E13
2,50	500	E16
4,00	500	E19
6,00	100	E22
10,00	100	E24
16,00	100	E26
25,00	50	E28
35,00	50	E30
50,00	50	E32